GENERAL SPECIFICATION

Approved to: EN60335-1:2002+A1,A2,A11,A12,A13,A14,A15 and EN60335-2-30:2009+A11
Power Rating: 200W/m²
Standard Voltage: 230V
Insulation Class: 2-double insulated
Thickness: 1 mm
IP Rating: 44
Cable connector: 30 x 40 x 5mm
Cable: 1m twin core 0.75mm² oval
Adhesive: acrylic
Material: Double insulated multi-layer polyester/polyethylene
Mirror temperature: Approximately 15ºC above ambient room temp.
Heating time: 3-5 Minutes depending on ambient room temperature
Heat spread: Approximately 30% area around the pad

***demista*™** Model Number	Nominal Power (Watts)	Dimensions(mm)	Resistance range (Ohms)	Current(Amps)
7060L025	28	600 X 250	1810 – 1900	0.12
7060L029	32	600 X 290	1551 – 1629	0.14
7060L033	37	600 X 330	1357 – 1425	0.16
7060L037	42	600 X 370	1206 – 1267	0.18
7060L041	46	600 X 410	1086 – 1140	0.20
7060L045	51	600 X 450	987 – 1036	0.22
7060L049	56	600 X 490	905 – 950	0.24
7060L053	60	600 X 530	835 – 877	0.26
7060L057	65	600 X 570	776 – 814	0.28
7060L061	70	600 X 610	724 – 760	0.30
7060L065	74	600 X 650	679 – 713	0.32
7060L069	79	600 X 690	639 – 671	0.34
7060L073	84	600 X 730	603 – 633	0.36
7060L077	88	600 X 770	571 – 600	0.38
7060L081	93	600 X 810	543 – 570	0.40
7060L085	97	600 X 850	517 – 543	0.42
7060L089	102	600 X 890	494 – 518	0.44
7060L093	107	600 X 930	472 – 496	0.46
7060L097	111	600 X 970	452 – 475	0.48
7060L101	116	600 X 1010	434 – 456	0.50
7060L105	121	600 X 1050	418 – 438	0.52
7060L109	125	600 X 1090	402 – 422	0.54
7060L113	130	600 X 1130	388 – 407	0.56
7060L117	135	600 X 1170	374 – 393	0.59
7060L121	139	600 X 1210	362 – 380	0.61

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_

7060L125	144	600 X 1250	350 – 368	0.63
7060L129	148	600 X 1290	339 – 356	0.65
7060L133	153	600 X 1330	329 – 345	0.67
7060L137	158	600 X 1370	319 – 335	0.69
7060L141	162	600 X 1410	310 – 326	0.71
7060L145	167	600 X 1450	302 – 317	0.73
7060L149	172	600 X 1490	293 – 308	0.75
7060L153	176	600 X 1530	286 – 300	0.77
7060L157	181	600 X 1570	278 – 292	0.79
7060L161	186	600 X 1610	271 – 285	0.81
7060L165	190	600 X 1650	265 – 278	0.83
7060L169	195	600 X 1690	259 – 271	0.85
7060L173	200	600 X 1730	253 – 265	0.87
7060L177	204	600 X 1770	247 – 259	0.89
7060L181	209	600 X 1810	241 – 253	0.91
7060L185	213	600 X 1850	236 – 248	0.93
7060L189	218	600 X 1890	231 – 243	0.95
7060L193	223	600 X 1930	226 – 238	0.97
7060L197	227	600 X 1970	222 – 233	0.99
7060L201	232	600 X 2010	217 – 228	1.01
7060L205	237	600 X 2050	213 – 224	1.03
7060L209	241	600 X 2090	209 – 219	1.05
7060L213	246	600 X 2130	205 – 215	1.07
7060L217	251	600 X 2170	201 – 211	1.09
7060L221	255	600 X 2210	197 – 207	1.11
7060L225	260	600 X 2250	194 – 204	1.13
7060L229	264	600 X 2290	190 – 200	1.15
7060L233	269	600 X 2330	187 – 197	1.17
7060L237	274	600 X 2370	184 – 193	1.19
7060L241	278	600 X 2410	181 – 190	1.21
7060L245	283	600 X 2450	178 – 187	1.23
7060L249	288	600 X 2490	175 – 184	1.25

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_