## GENERAL SPECIFICATION

**Approved to:** EN60335-1:2002+A1,A2,A11,A12,A13,A14,A15 and EN60335-2-30:2009+A11
**Power Rating:** 200W/m²
**Standard Voltage:** 230V
**Insulation Class:** 2-double insulated
**Thickness:** 1 mm
**IP Rating:** 44
**Cable connector:** 30 x 40 x 5mm
**Cable:** 1m twin core 0.75mm² oval
**Adhesive:** acrylic
**Material:** Double insulated multi-layer polyester/polyethylene
**Mirror temperature:** Approximately 15ºC above ambient room temp.
**Heating time:** 3-5 Minutes depending on ambient room temperature
**Heat spread:** Approximately 30% area around the pad

| ***demista*™** Model Number | Nominal Power (Watts) | Dimensions(mm) | Resistance range (Ohms) | Current(Amps) |
|---|---|---|---|---|
| 7070L025 | 33 | 700 X 250 | 1544 – 1621 | 0.14 |
| 7070L029 | 38 | 700 X 290 | 1323 – 1389 | 0.17 |
| 7070L033 | 44 | 700 X 330 | 1158 – 1216 | 0.19 |
| 7070L037 | 49 | 700 X 370 | 1029 – 1080 | 0.21 |
| 7070L041 | 54 | 700 X 410 | 926 – 972 | 0.24 |
| 7070L045 | 60 | 700 X 450 | 842 – 884 | 0.26 |
| 7070L049 | 65 | 700 X 490 | 772 – 810 | 0.28 |
| 7070L053 | 71 | 700 X 530 | 712 – 748 | 0.31 |
| 7070L057 | 76 | 700 X 570 | 662 – 695 | 0.33 |
| 7070L061 | 82 | 700 X 610 | 617 – 648 | 0.35 |
| 7070L065 | 87 | 700 X 650 | 579 – 608 | 0.38 |
| 7070L069 | 92 | 700 X 690 | 545 – 572 | 0.40 |
| 7070L073 | 98 | 700 X 730 | 515 – 540 | 0.43 |
| 7070L077 | 103 | 700 X 770 | 487 – 512 | 0.45 |
| 7070L081 | 109 | 700 X 810 | 463 – 486 | 0.47 |
| 7070L085 | 114 | 700 X 850 | 441 – 463 | 0.50 |
| 7070L089 | 120 | 700 X 890 | 421 – 442 | 0.52 |
| 7070L093 | 125 | 700 X 930 | 403 – 423 | 0.54 |
| 7070L097 | 131 | 700 X 970 | 386 – 405 | 0.57 |
| 7070L101 | 136 | 700 X 1010 | 370 – 389 | 0.59 |
| 7070L105 | 141 | 700 X 1050 | 356 – 374 | 0.61 |
| 7070L109 | 147 | 700 X 1090 | 343 – 360 | 0.64 |
| 7070L113 | 152 | 700 X 1130 | 331 – 347 | 0.66 |
| 7070L117 | 158 | 700 X 1170 | 319 – 335 | 0.69 |
| 7070L121 | 163 | 700 X 1210 | 309 – 324 | 0.71 |

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_

| | | | | |
|---|---|---|---|---|
| 7070L125 | 169 | 700 X 1250 | 299 – 314 | 0.73 |
| 7070L129 | 174 | 700 X 1290 | 289 – 304 | 0.76 |
| 7070L133 | 180 | 700 X 1330 | 281 – 295 | 0.78 |
| 7070L137 | 185 | 700 X 1370 | 272 – 286 | 0.80 |
| 7070L141 | 190 | 700 X 1410 | 265 – 278 | 0.83 |
| 7070L145 | 196 | 700 X 1450 | 257 – 270 | 0.85 |
| 7070L149 | 201 | 700 X 1490 | 250 – 263 | 0.88 |
| 7070L153 | 207 | 700 X 1530 | 244 – 256 | 0.90 |
| 7070L157 | 212 | 700 X 1570 | 237 – 249 | 0.92 |
| 7070L161 | 218 | 700 X 1610 | 232 – 243 | 0.95 |
| 7070L165 | 223 | 700 X 1650 | 226 – 237 | 0.97 |
| 7070L169 | 228 | 700 X 1690 | 221 – 232 | 0.99 |
| 7070L173 | 234 | 700 X 1730 | 215 – 226 | 1.02 |
| 7070L177 | 239 | 700 X 1770 | 210 – 221 | 1.04 |
| 7070L181 | 245 | 700 X 1810 | 206 – 216 | 1.06 |
| 7070L185 | 250 | 700 X 1850 | 201 – 211 | 1.09 |
| 7070L189 | 256 | 700 X 1890 | 197 – 207 | 1.11 |
| 7070L193 | 261 | 700 X 1930 | 193 – 203 | 1.14 |
| 7070L197 | 267 | 700 X 1970 | 189 – 198 | 1.16 |
| 7070L201 | 272 | 700 X 2010 | 185 – 194 | 1.18 |
| 7070L205 | 277 | 700 X 2050 | 182 – 191 | 1.21 |
| 7070L209 | 283 | 700 X 2090 | 178 – 187 | 1.23 |
| 7070L213 | 288 | 700 X 2130 | 175 – 183 | 1.25 |
| 7070L217 | 294 | 700 X 2170 | 172 – 180 | 1.28 |
| 7070L221 | 299 | 700 X 2210 | 168 – 177 | 1.30 |
| 7070L225 | 305 | 700 X 2250 | 165 – 174 | 1.32 |
| 7070L229 | 310 | 700 X 2290 | 162 – 171 | 1.35 |
| 7070L233 | 316 | 700 X 2330 | 160 – 168 | 1.37 |
| 7070L237 | 321 | 700 X 2370 | 157 – 165 | 1.40 |
| 7070L241 | 326 | 700 X 2410 | 154 – 162 | 1.42 |
| 7070L245 | 332 | 700 X 2450 | 152 – 159 | 1.44 |
| 7070L249 | 337 | 700 X 2490 | 149 – 157 | 1.47 |

**10 year** warranty against any manufacturing fault, providing ***demista™*** is fitted strictly in accordance with instructions supplied.

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_