GENERAL SPECIFICATION

Approved to: EN60335-1:2002+A1,A2,A11,A12,A13,A14,A15 and EN60335-2-30:2009+A11
Power Rating: 200W/m²
Standard Voltage: 120V
Insulation Class: 2-double insulated
Thickness: 1 mm
IP Rating: 44
Cable connector: 30 x 40 x 5mm
Cable: 1m twin core 0.75mm² oval
Adhesive: acrylic
Material: Double insulated multi-layer polyester/polyethylene
Mirror temperature: Approximately 10 -15ºC above ambient room temp.
Heating time: 3-5 minutes to start to heat the mirror (depending on ambient room temperature)
Heat spread: Approximately 30% area around the pad

***demista*™** Model Number	Nominal Power (Watts)	Dimensions(mm)	Resistance range (Ohms) +-10%	Current (Amps)
7105	7	274mm X 150mm	2304	0.06
7110	15	274mm X 265mm	960	0.12
7120	25	584MM x 274mm	576	0.22
7125	36	462mm X 424mm	400	0.32
7130	50	524mm X 520mm	288	0.434
7133	43	800mm X 300mm	335	0.374
7135	80	785mm X 524mm	185	0.70
7140	100	1040mm X 524mm	144	0.86
7150	150	1505mm X 524mm	96	1.30

10 year warranty against any manufacturing fault, providing ***demista*™** is fitted strictly in accordance with instructions supplied.

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_