GENERAL SPECIFICATION

Approved to: EN60335-1:2002+A1,A2,A11,A12,A13,A14,A15 and EN60335-2-30:2009+A11
Power Rating: 200W/m²
Standard Voltage: 230V
Insulation Class: 2-double insulated
Thickness: 1 mm
IP Rating: 44
Cable connector: 30 x 40 x 5mm
Cable: 1m twin core 0.75mm² oval
Adhesive: acrylic
Material: Double insulated multi-layer polyester/polyethylene
Mirror temperature: Approximately 15ºC above ambient room temp.
Heating time: 3-5 Minutes depending on ambient room temperature
Heat spread: Approximately 30% area around the pad

***demista*™** Model Number	Nominal Power (Watts)	Dimensions(mm)	Resistance range (Ohms)	Current(Amps)
7015L025	6	150 X 250	8074 – 9420	0.03
7015L029	7	150 X 290	6920 – 7266	0.03
7015L033	8	150 X 330	6055 – 6358	0.04
7015L037	9	150 X 370	5383 – 5652	0.04
7015L041	10	150 X 410	4844 – 5087	0.05
7015L045	11	150 X 450	4404 – 5138	0.05
7015L049	12	150 X 490	4037 – 4239	0.05
7015L053	14	150 X 530	3726 – 3913	0.06
7015L057	15	150 X 570	3460 – 4037	0.06
7015L061	16	150 X 610	3230 – 3391	0.07
7015L065	17	150 X 650	3028 – 3179	0.07
7015L069	18	150 X 690	2850 – 3325	0.08
7015L073	19	150 X 730	2691 – 2826	0.08
7015L077	20	150 X 770	2550 – 2677	0.09
7015L081	21	150 X 810	2422 – 2826	0.09
7015L085	22	150 X 850	2307 – 2422	0.09
7015L089	23	150 X 890	2202 – 2569	0.10
7015L093	24	150 X 930	2106 – 2212	0.10
7015L097	25	150 X 970	2018 – 2355	0.11
7015L101	26	150 X 1010	1938 – 2035	0.11
7015L105	27	150 X 1050	1863 – 2174	0.12
7015L109	28	150 X 1090	1794 – 1884	0.12
7015L113	29	150 X 1130	1730 – 1817	0.13
7015L117	30	150 X 1170	1670 – 1949	0.13
7015L121	31	150 X 1210	1615 – 1696	0.14
7015L125	32	150 X 1250	1563 – 1641	0.14

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_

7015L129	33	150 X 1290	1514 – 1766	0.14
7015L133	34	150 X 1330	1468 – 1541	0.15
7015L137	35	150 X 1370	1425 – 1662	0.15
7015L141	36	150 X 1410	1384 – 1453	0.16
7015L145	37	150 X 1450	1346 – 1413	0.16
7015L149	38	150 X 1490	1309 – 1527	0.17
7015L153	40	150 X 1530	1275 – 1339	0.17
7015L157	41	150 X 1570	1242 – 1304	0.18
7015L161	42	150 X 1610	1211 – 1413	0.18
7015L165	43	150 X 1650	1182 – 1241	0.19
7015L169	44	150 X 1690	1153 – 1211	0.19
7015L173	45	150 X 1730	1127 – 1183	0.19
7015L177	46	150 X 1770	1101 – 1156	0.20
7015L181	47	150 X 1810	1077 – 1256	0.20
7015L185	48	150 X 1850	1053 – 1106	0.21
7015L189	49	150 X 1890	1031 – 1202	0.21
7015L193	50	150 X 1930	1009 – 1060	0.22
7015L197	51	150 X 1970	989 – 1038	0.22
7015L201	52	150 X 2010	969 – 1130	0.23
7015L205	53	150 X 2050	950 - 997	0.23
7015L209	54	150 X 2090	932 - 1087	0.24
7015L213	55	150 X 2130	914 – 960	0.24
7015L217	56	150 X 2170	897 – 942	0.24
7015L221	57	150 X 2210	881 - 1028	0.25
7015L225	58	150 X 2250	865 – 908	0.25
7015L229	59	150 X 2290	850 - 992	0.26
7015L233	60	150 X 2330	835 – 877	0.26
7015L237	61	150 X 2370	821 – 862	0.27
7015L241	62	150 X 2410	807 – 942	0.27
7015L245	63	150 X 2450	794 – 834	0.28
7015L249	64	150 X 2490	781 – 912	0.28

10 year warranty against any manufacturing fault, providing ***demista™*** is fitted strictly in accordance with instructions supplied.

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_