GENERAL SPECIFICATION

Approved to: EN60335-1:2002+A1,A2,A11,A12,A13,A14,A15 and EN60335-2-30:2009+A11
Power Rating: 200W/m²
Standard Voltage: 230V
Insulation Class: 2-double insulated
Thickness: 1 mm
IP Rating: 44
Cable connector: 30 x 40 x 5mm
Cable: 1m twin core 0.75mm² oval
Adhesive: acrylic
Material: Double insulated multi-layer polyester/polyethylene
Mirror temperature: Approximately 15ºC above ambient room temp.
Heating time: 3-5 Minutes depending on ambient room temperature
Heat spread: Approximately 30% area around the pad

***demista*™** Model Number	Nominal Power (Watts)	Dimensions(mm)	Resistance range (Ohms)	Current(Amps)
7030L025	13	300 X 250	3749 – 3936	0.06
7030L029	16	300 X 290	3213 - 3374	0.07
7030L033	18	300 X 330	2811 – 2952	0.08
7030L037	20	300 X 370	2499 – 2624	0.09
7030L041	22	300 X 410	2249 – 2362	0.10
7030L045	25	300 X 450	2045 – 2147	0.11
7030L049	27	300 X 490	1874 – 1968	0.12
7030L053	29	300 X 530	1730 – 1817	0.13
7030L057	31	300 X 570	1607 – 1687	0.14
7030L061	34	300 X 610	1499 – 1574	0.15
7030L065	36	300 X 650	1406 – 1476	0.16
7030L069	38	300 X 690	1323 – 1389	0.17
7030L073	40	300 X 730	1250 – 1312	0.18
7030L077	43	300 X 770	1184 – 1243	0.19
7030L081	45	300 X 810	1125 – 1181	0.19
7030L085	47	300 X 850	1071 – 1125	0.20
7030L089	49	300 X 890	1022 – 1073	0.21
7030L093	52	300 X 930	978 – 1027	0.22
7030L097	54	300 X 970	937 – 984	0.23
7030L101	56	300 X 1010	900 – 945	0.24
7030L105	58	300 X 1050	865 – 908	0.25
7030L109	60	300 X 1090	833 – 875	0.26
7030L113	63	300 X 1130	803 – 843	0.27
7030L117	65	300 X 1170	776 – 814	0.28
7030L121	67	300 X 1210	750 – 787	0.29

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_

7030L125	69	300 X 1250	726 – 762	0.30
7030L129	72	300 X 1290	703 – 738	0.31
7030L133	74	300 X 1330	682 – 716	0.32
7030L137	76	300 X 1370	662 – 695	0.33
7030L141	78	300 X 1410	643 – 675	0.34
7030L145	81	300 X 1450	625 – 656	0.35
7030L149	83	300 X 1490	608 – 638	0.36
7030L153	85	300 X 1530	592 – 621	0.37
7030L157	87	300 X 1570	577 – 606	0.38
7030L161	90	300 X 1610	562 – 590	0.39
7030L165	92	300 X 1650	549 – 576	0.40
7030L169	94	300 X 1690	536 – 562	0.41
7030L173	96	300 X 1730	523 – 549	0.42
7030L177	99	300 X 1770	511 – 537	0.43
7030L181	101	300 X 1810	500 – 525	0.44
7030L185	103	300 X 1850	489 – 513	0.45
7030L189	105	300 X 1890	479 – 502	0.46
7030L193	108	300 X 1930	469 – 492	0.47
7030L197	110	300 X 1970	459 – 482	0.48
7030L201	112	300 X 2010	450 – 472	0.49
7030L205	114	300 X 2050	441 – 463	0.50
7030L209	116	300 X 2090	433 – 454	0.51
7030L213	119	300 X 2130	424 – 446	0.52
7030L217	121	300 X 2170	417 – 437	0.53
7030L221	123	300 X 2210	409 – 429	0.54
7030L225	125	300 X 2250	402 – 422	0.55
7030L229	128	300 X 2290	395 – 414	0.56
7030L233	130	300 X 2330	388 – 407	0.56
7030L237	132	300 X 2370	381 – 400	0.57
7030L241	134	300 X 2410	375 – 394	0.58
7030L245	137	300 X 2450	369 – 387	0.59
7030L249	139	300 X 2490	363 - 381	0.60

10 year warranty against any manufacturing fault, providing ***demista™*** is fitted strictly in accordance with instructions supplied.

All rights reserved. All copyrights and trademarks acknowledged. Specifications subject to change without notice.

Web: www.neo2c.com
Email: info@neo2c.com
Tel.: +44 (0) 20 7310 8005

Neo2c supply an extensive range of guest connectivity products. Please contact us for further options.

@NEO2CHOSPITALITY @NEO2C @NEO2C_