neo2c teleadapt

Bringing hospitality together

ChargePort Pro Universal TA-7820

Desktop power and charging for hotel guest rooms.

Sleek, Stylish Design

ChargePort Pro Universal is sleek and stylish to blend easily with your décor choices and is available in either black or grey. Use of the latest integrated GaN power supply technology ensures minimum size and maximum efficiency and power output.

Dual Mains Outlets and Qi

ChargePort Pro Universal features dual shuttered universal mains outlets which are rotated to maximise flexibility and can supply a total of up to 10A.

The top surface has an integrated 10W Qi wireless charging pad. Simply place your Qi compatible smartphone on the charging pad to enable charging.

Triple USB Charging

Dual USB-C outlets can charge up to 45 watts (shared) for smartphones, tablets and laptops. In addition charge at up to 12W using USB Type-A which is ideal for charging smartphones and tablets.

Socket for Power Cable

The inline C14 socket on a 2ft (0.61m) flying lead allows you to easily attach a suitable power cable.

Security Options

For additional security choose from a cable clamp, adhesive pad or security lanyard.

Specifications

- Durable construction designed for everyday use.
- 2 x shuttered universal outlets, 120V/240V (depending on input), 10A shared max.
- Rotated mains outlet layout for maximum flexibility.
- Integrated GaN power supply for minimum size and maximum efficiency and power.
- 10W Qi Certified wireless charging pad with Foreign Object Detection (FOD).
- 2 x USB-C charging sockets, PD/PPS.
  Single use:
  USB-C1: 5V/3A, 9V/3A, 15V/3A, 20V/2.25A. PPS： 5V-16V/3A, 5V-21V/2.25A (45W Max).
  USB-C2： 5V/3A, 9V/3A, 15V/3A, 20V/2.25A. PPS： 5V-16V/3A, 5V-21V/2.25A (45W Max).
  Dual use:
  USB-C1: 5V/3A, 9V/3A, 15V/2A, 20V/1.5A. PPS:5V-11V/3A (30W Max).
  USB-C2: 5V/3A,9V/1.67A (15W).
- 1 x USB-A charging socket. 5V, 2.4A.
- 67W maximum, 2 x USB-C 45W (shared),1 x USB-A 12W, 10W Qi.
- Input 120V/240V 15A via 200mm flying lead with a C14 inline socket.
- Built-in overload protection.
- Pass-through plug replaces wall outlet used to install.
- Certified to FCC part 15, sub part b and WPC Qi 1.3.
- Security options include cable clamp, adhesive pad and security lanyard.

Dimensions



A. 2 x universal outlets.
B. 10W certified Qi charging pad.
C. 2 x USB-Type-C® and 1 x USB-A charging.

Part Numbers

TA-7820U-D2-AS
ChargePort Pro Universal, with C14 socket, black, 2ft (0.61m).

TA-7820U-D2-BS
ChargePort Pro Universal, with C14 socket, black/grey, 2ft (0.61m).

neo2c
Bringing hospitality together

Email: info@neo2c.com
Tel: +44 (0) 207 310 8005
Website: https://www.neo2c.com

@NEO2CHOSPITALITY
@NEO2C
@NEO2C_